



# Thermocouples



T and J type thermocouples for use with thermocouple systems like XpertVal®.



Name	Reference	Max. Temp.	Description
Bundle of 20 premium Type T thermocouples, 24 gauge, 7 stranded	T-24-TT-7S-20-10	200°C	Teflon coated, 32 feet (10 m) length, harnessed, numbered and labeled. One inch Teflon coated welded tip
Bundle of 20 premium Type T thermocouples, 24 gauge	T-24-TT-20-10	200°C	Teflon coated, 32 feet (10 m) length, harnessed, numbered and labeled. One inch Teflon coated welded tip
Roll of premium Type T thermocouples, 24 gauge	RL-24-TT-1000	200°C	Teflon coated, 1000 feet (300 m) length
Roll of Premium Type T thermocouples, 24 gauge	RL-24-KK-1000	350°C	Kapton coated, 1000 feet (300 m) length
Bundle of 20 premium Type T 24 gauge, kapton coated	T-24-KK-20-10	350°C	Kapton coated, 32 feet(10m) length, harnessed, numbered and labeled
Bundle of 20 premium Type J thermocouples, 24 gauge	J-24-KK-20-10	400°C	Kapton coated, 32 feet (10 m) length, harnessed, numbered and labeled, each thermocouple with welded tip
Bundle of 20 premium Type T thermocouples, 24 gauge (needle tip)	NT-24-TT-20-10	200°C	Teflon coated, 32 feet (10m) length, harnessed, numbered and labeled, each thermocouple with needle tip
CUSTOM: Bundle of xx premium Type T/J thermocouples, teflon / kapton coated	T-24-TT-xx-yy T-24-KK-xx-yy J-24-KK-xx-yy	200°C 350°C 400°C	Custom teflon / kapton coated, yy m length, harnessed, numbered and labeled, each thermocouple with welded tip

For best performance we recommend XpertVal® with wireless capability.



XpertLog®

XpertVal®

