



## PTC Dry Blocks



The PTC Series matches lab features like a wide temperature range, high accuracy, stability, and speed. The PTC Series features an active dual zone temperature control which provides excellent temperature homogeneity in the well.

This PTC series is included in the close loop calibration feature provided by Xpertlog software.

Name	References	Range	Stability	Delivered with	Ref. probe
PTC-125A Ultra Cooler Dry Block	PTC-125A_Lives_230A_NON_F PTC-125A_Lives_115B_NON_F	-90 to 125 °C -130 to 257 °F	± 0.03 °C		- Internal
PTC-125C Ultra Cooler Dry Block	PTC-125C_Lives_230A_NON_R16_126394-901_HS_CT PTC-125C_Lives_115B_NON_R16_126394-901_HS_CT	-90 to 125 °C -130 to 257 °F	± 0.03 °C	- Accredited System Calibration	- External - Internal
PTC-155A Cooler Dry Block	PTC-155A_Lives230A_NON_F_CT PTC-155A_Lives115B_NON_F_CT	-25 to 155 °C -13 to 311°F	± 0.01 °C		- Internal
PTC-155C Cooler Dry Block	PTC-155C_Lives230A_NON_R_126394-901_HS_CT PTC-155C_Lives115B_NON_R_126394-901_HS_CT	-25 to 155 °C -13 to 311°F	± 0.01 °C	- Accredited System Calibration	- External - Internal
PTC-350A Dry Block	PTC-350A_Lives_230A_NON_F PTC-350A_Lives_115B_NON_F	33 to 350 °C 91 to 662 °F	± 0.02 °C		- Internal
PTC-350C Dry Block	PTC-350C_Lives_230A_NON_R12_915_HS_CT PTC-350C_Lives_115B_NON_R12_915_HS_CT	33 to 350 °C 91 to 662 °F	± 0.02 °C	- Accredited System Calibration	- External - Internal
PTC-425A Dry Block	PTC-425A_Lives_230_A_NON_F_CT PTC-425A_Lives_115_B_NON_F_CT	33 to 425 °C 91 to 797 °F	± 0.02 °C		- Internal
PTC-425C Dry Block	PTC-425C_Lives_230_A_NON_R13_915_HS_CT PTC-425C_Lives_115_B_NON_R13_915_HS_CT	33 to 425 °C 91 to 797 °F	± 0.02 °C	- Accredited System Calibration	- External - Internal
PTC-660A Dry Block	PTC-660A_Lives_230_A_NON_F PTC-660A_Lives_115B_NON_F	33 to 660 °C 91 to 1220 °F	± 0.04 °C		- Internal
PTC-660C Dry Block	PTC-660C_Lives_230A_NON_R13_915_HS_CT PTC-660C_Lives_115B_NON_R13_915_HS_CT	33 to 660 °C 91 to 1220 °F	± 0.04 °C	- Accredited System Calibration	- External - Internal

All PTC dry blocks are delivered with carrying case with trolley. Insert is not included.