





# GMP RF F 30H



## Real Time Wireless Temperature Data Logger with Flexible Sensor -90°C to +140°C



- + Collects and transmits real time temperature to XpertLog Software
- + ITS-90 calibration coefficients are stored in the internal memory
- + Complies with FDA 21 CFR Part 11
- + Network ready: multiple users, centralized, server database, active directory authentication
- + Calibration can be performed on site
- + Can be remotely activated



Sensor type	4 wires
- flexible	4 wires: 430 mm (17")
- customized	up to 5000 mm (195")
- Sensor size	1.5 x 8 mm (0.06 x 0.315")
- cross section	1.77 mm <sup>2</sup> (0.0027 inch <sup>2</sup> )
Operating Range	
- body	-90°C to +140°C
- Sensor	-200°C to +200°C
Accuracy	±0.1°C from -90°C to +140°C
Resolution	0.01°C
Memory capacity	32,000 data points
Memory type	non volatile
Sampling rate	1 sec to 24 hours
Transmission	simultaneous: maximum 20 loggers sequential: unlimited
Internal clock drift	4 sec / 24 h @ 23°C
Mechanical	
- material	Peek 1000 - FDA compliant
- enclosure	IP-68
- weight	50 g (1.76 oz)
- diameter	37 mm (1.46")
- height	62.81 mm (2.47")
Power	2 x Lithium batteries, 0.35 g/each Lithium content classified UN3091 under IATA DGR section 3.9.2.6 compliant with ICAO/IATA packing instructions 970, user replaceable Up to 6 months, based on usage
Battery lifetime	Internal
Antenna	121 m (400 feet)
Wireless range	2.4 Ghz ISM band
Radio frequency	USB to computer
Access point	Programs and reads unlimited number of loggers
Calibrations	Factory Calibrations: traceable NIST/COFRAC - ITS-90 coefficients stored in the internal memory User Calibrations: closed loop calibration using XpertLog® software
Certification	Health Safety: EN 60950-1 / 2006 EMC: EN 60601-1-2 / 2007 RF: EN 300440-2 v1.3.1 (2009-03)

### Order Reference

GMP-RF-F-30H  
GMP-RF-F-30H-2m  
GMP-RF-F-30H-3m  
GMP-RF-F-30H-4m  
GMP-RF-F-30H-5m

### Standard Calibration Points

- -80°C
- 0°C
- 140°C



XpertLog  
software

